



Queensland Gate Automation

Ph: 07 3085 8750

Email: [sales@gga.com.au](mailto:sales@gga.com.au)

**CENTSYS SMARTGUARD WIRELESS KEYPAD – CHEAT SHEET**

<b>Smartguard Wireless Keypad</b>	<b>Changing the Master Code – Quick Code Change for Single Code</b>
	<ol style="list-style-type: none"> <li>1) Enter *1234* <i>OR mastercode if it has been changed from 1234</i></li> <li>2) Enter 0#</li> <li>3) Enter 0#</li> <li>4) Enter new code followed by # (this will now be the new master code)</li> </ol>
<b>Smartguard Wireless Keypad</b>	<b>Adding Additional Users</b>
	<ol style="list-style-type: none"> <li>1) Enter *master code*</li> <li>2) Enter 1#</li> <li>3) Enter 2# (for second user added <i>the master user being user 1, 3# for third user etc</i>)</li> <li>4) Enter code to be added followed by #</li> <li>5) Enter 1# (this represents channel 1 which is usually the channel to trigger the gate normally – <b>if doing a second gate off the same keypad or a separate function such as a pedestrian function then enter 2# for channel two</b>)</li> <li>6) Enter ###</li> </ol>
<b>Smartguard Wireless Keypad</b>	<b>Pairing the Unit to the Gate Motor</b>
	<p><b>D5 Evo and Vector / Vantage Series</b></p> <ol style="list-style-type: none"> <li>1) Go to the control panel of the motor</li> <li>2) In the settings area go to “Remote Controls”</li> <li>3) Select “Add Remote – Select Function Trigger Gate”</li> <li>4) When it says “Push Remote Button” enter the code on the keypad followed by the # key</li> </ol> <p><b>D2 Turbo</b></p> <ol style="list-style-type: none"> <li>1) Go to the control panel of the motor</li> <li>2) Turn the function knob to B – Remotes</li> <li>3) Turn the settings knob to the far left – TGR Gate</li> <li>4) Push the status button and the led will change to green</li> <li>5) Enter the code on the keypad followed by the # key – you should here two little acknowledgment beeps from the control panel</li> <li>6) Turn the function knob back to Run</li> </ol>



Queensland Gate Automation

Ph: 07 3085 8750

Email: [sales@gga.com.au](mailto:sales@gga.com.au)

**CENTSYS SMARTGUARD WIRELESS KEYPAD – CHEAT SHEET**

Smartguard Wireless Keypad	To Reset The Panel to Factory Default
	<p>Defaulting the Master Code</p> <ol style="list-style-type: none"><li>1) Remove power by removing 1 battery</li><li>2) Hold down button 1</li><li>3) Reapply power by reinserting the battery while continuing to hold down button 1</li><li>4) After 2 seconds the unit will beep indicating that the master code has been reset to 1234#.</li><li>5) Release button 1</li></ol> <p>Defaulting the System Parameters (Factory Default)</p> <ol style="list-style-type: none"><li>1) Remove power by removing 1 battery</li><li>2) Hold down buttons 2 and 3 together</li><li>6) Reapply power by reinserting the battery while continuing to hold down buttons 2 and 3</li><li>7) After 2 seconds the unit will beep indicating that the panel has been reset to factory default.</li></ol> <p><b>Keypad will need to be repaired to the motor in the same manner as adding a remote.</b></p>